

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



Ar

(11)

EP 0 869 022 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
07.10.1998 Bulletin 1998/41

(51) Int. Cl.<sup>6</sup>: B60K 15/035, F02M 25/08

(21) Application number: 97310702.2

(22) Date of filing: 31.12.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 31.03.1997 US 829664

(71) Applicant: Ford Motor Company  
Dearborn, MI 48126 (US)

(72) Inventors:  
• Stringfellow, George Francis  
Dearborn Heights, Michigan 48127 (US)  
• Ayers, Douglas William  
Milan, Michigan 48160 (US)  
• Nulman, Mark  
West Bloomfield, Michigan 48322 (US)

(74) Representative:  
Messulam, Alec Moses et al  
A. Messulam & Co.  
24 Broadway  
Leigh-on-Sea Essex SS9 1BN (GB)

### (54) Fuel tank vapour control apparatus

(57) A fuel tank vapour control apparatus controls the flow of liquid and vapour fuel through an aperture in a fuel tank (16). The fuel tank vapour control apparatus includes a vent housing (12) mounted in the aperture (34) and formed to include a vent inlet (13) and a vent outlet (36), the vent housing (12) defining a vent path for communicating vapour fuel from the fuel tank between the vent inlet and the vent outlet. The apparatus also includes a valve (48) movable in the vent housing between a blocking position for blocking flow of liquid and vapour fuel from the fuel tank between the vent inlet and the vent outlet along the vent path and a venting position allowing flow of vapour fuel between the fuel tank and the vent outlet along the vent path. A labyrinthine member (140) is also included, being disposed between the fuel tank and the vent path for discriminating fuel vapour from liquid fuel so as to block liquid fuel from the vent path.




FIG.2

## Description

This invention relates generally to fuel tank venting devices for controlling the flow of fuel vapours in a motor vehicle fuel delivery system. More particularly, the present invention relates to a fuel tank vapour control system that resists inadvertent vent valve closures due to fuel slosh.

It is well known to provide controlled venting of fuel vapours within a fuel tank of a motor vehicle to maintain internal tank pressures at a predetermined level. Fuel vapours may be created in the fuel tank as a result of temperature differences in the vapour space and the fuel itself, as well as by sloshing and agitation of the fuel during normal operation of the vehicle. The pressure generated from the resultant vapour generation is relieved by venting the pressure to atmosphere. Traditional vapour vents include design provisions to prevent the passage of liquid fuel.

In the traditional fuel system, provisions were made for recovering the fuel from the vapours and returning the liquid fuel to the fuel tank. It has been discovered that the vapours can be routed to the intake manifold of the internal combustion engine for direct consumption by the engine. This has presented a challenge in that previously, if fuel slosh caused the vapour vent valve to close, the discontinuous flow of fuel vapour had no consequences, now it can result in irregular fuel delivery to the engine, which in some instances may cause a rough running engine condition.

It would therefore be desirable to provide a fuel tank vapour control system less sensitive to liquid fuel contacting the vapour vent valve, such that inadvertent interruptions of vapour deliver to the engine may be minimised.

According to the present invention, a fuel tank vapour control apparatus for controlling the flow of liquid and vapour fuel through an aperture in a fuel tank has been discovered for isolating a fuel valve from transient liquid fuel contact, thereby reducing interruptions of fuel vapour delivery to an internal combustion engine. The fuel tank vapour control apparatus includes a vent housing mounted in the aperture and formed to include a vent inlet and a vent outlet and defining a vent path for communicating vapour fuel from the fuel tank between the vent inlet and the vent outlet.

A valve is movably located in the vent housing between a blocking position for blocking flow of liquid and vapour fuel from the fuel tank between the vent inlet and the vent outlet along the vent path and a venting position for allowing flow of vapour fuel between the fuel tank and the vent outlet along the vent path. The apparatus also includes a labyrinthine member disposed between the fuel tank and the vent path allowing vapour fuel to flow in the vent path and blocking liquid fuel flow in the vent path.

Advantageously, the surface tension of the liquid fuel closes the open cells in the foam, creating a restric-

tion to the passage of liquid fuel, preventing intermittent interruptions of vapour flow through this vapour vent valve.

The invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is schematic view of a fuel tank vapour control apparatus constructed in accordance with the present invention;

Figure 2 is a cross-sectional view taken from Figure 1 of a fuel tank vapour control apparatus in an open state according to the present invention;

Figure 3 is a cross-sectional view taken from Figure 1 of a fuel tank vapour control apparatus in a closed state according to the present invention; and

Figure 4 is a view of a foam member having open cell structure for use in a fuel tank vapour control apparatus in accordance with the present invention.

Referring now to FIGS. 1 and 2, a fuel tank vapour control apparatus includes a vent housing 12 having a vent inlet 13 disposed in a fuel tank 16 and in fluid communication with a fuel vapour treatment device 22, such as a charcoal filled vapour recovery canister. The canister 22 receives the vapours from the vent housing 12 through a canister inlet 18 and communicates those vapours through a canister outlet 20 to a vapour purge valve 24, which receives control signals from an engine controller 26. The vapour purge valve 24 is also in fluid communication with an intake manifold 30 of an internal combustion engine 32. The engine controller 26 also generates control signals for the primary fuel delivery system, which in part depends on the control signal generated for the vapour purge valve 24.

As shown in FIG. 2, vent housing apparatus 12 is designed to be mounted in an aperture 34 formed in a top wall 17 of the fuel tank. Housing 12 is formed to include a hollow interior which is divided into a lower chamber 25 and an upper chamber 27 by a flow shield 28. Lower chamber 25 houses a rollover valve assembly 31, while upper chamber 26 houses valve assembly 33.

Housing 12 is formed to include a valve inlet 35 which allows fuel vapour from the fuel tank to pass into upper chamber 27. Valve inlet 35 is sized to permit relatively large volumes of fuel vapour to pass into upper chamber 27 for eventual venting past the valve 33 to canister 22 as will be subsequently described. Depending on the size of the fuel tank, it may be desirable to include a plurality of valve inlets to provide adequate vapour flow. Housing 12 is also formed to include a vent outlet 36 which allows passage of fuel vapour from housing 12 to the canister inlet 18. Housing 12 thus defines a vent path for fuel vapours 37 to flow between the fuel tank 16 and outlet 36.

The flow of fuel vapour along the vent path is controlled by valve assembly 33. Valve assembly 33 includes a valve 48 and a valve actuator 50. Valve 48 is

typically of the variety of valves known as "poppet" valves.

Referring now to FIGS. 2 and 3, valve 48 is moveable between a blocking position (shown in FIG. 3) and a venting position (shown in FIG. 2). Valve assembly 33 also includes a spring 52 acting between flow shield 28 and valve 48 to bias valve 48 towards its blocking position. Valve 48, when thus seated, blocks flow of fuel vapour between the fuel tank and outlet 36 along the vent path. When moved away from its blocking position to its venting position, valve 48 allows flow of fuel vapour between the fuel tank and outlet 36 along the vent path.

Valve actuator 50 is provided to move valve 48 from its blocking position against spring 52 to its venting position when the fuel vapour pressure in the fuel tank exceeds a predetermined level. Fuel vapour from the fuel tank is used to depress valve actuator 50, which in turn urges valve 48 toward its venting position shown in FIG. 2.

Diaphragm 64 is movable in response to an accumulation of fuel vapour pressure in venting control chamber 62 between a static position allowing valve 48 to remain in its blocking position and an actuating position urging valve 48 against the bias of spring 52 toward its venting position.

The fuel tank vapour control system is also provided with rollover valve assembly 31 as previously noted. Although any of a number of designs may be used, a preferred rollover valve assembly includes a float valve 102 or other liquid discriminator provided with a captured stainless steel ball 104 for inertial actuation of the float valve. Float valve 102 includes a nipple 103 to seat in sealing engagement with a surface 105 to block the flow of fuel vapour and liquid fuel from lower chamber 25 through inlet opening 88.

In particular, rollover valve assembly 31 includes, in addition to float valve 102 and captured ball 104, a retainer 108 and a support assembly 110. Float valve 102 cooperates with support assembly 110 to define a float chamber 107 in which ball 104 is positioned. Retainer 108 is designed to snap fit into openings 112 formed in housing 12. Retainer 108 also includes a plurality of vertically extending fins 114 positioned in approximately equally spaced intervals about the circumference of retainer 108. Support assembly 110 further includes a curved upper surface 134 providing a seat for ball 104 to insure proper camming relationship between ball 104 and support assembly 110. The curvature of curved upper surface 134 may be varied according to design considerations. For example, the curvature might be varied so that float valve 102 remains in its open position as the vehicle is subjected to a grade of less than or equal some predetermined amount. A plurality of openings 126 may be formed on support assembly 110 in approximately equally spaced intervals about curved upper surface 134, allowing passage of a limited amount of fuel vapour therethrough.

A labyrinthine member, such as a block of foam 140

having open cell structure 144, as can best be seen in FIG. 4, of sufficient size to envelope the desired valve inlets is attached to the valve housing 12 with outwardly projecting barbs 142. Alternatively, the foam could be attached using an adhesive or a strap. The foam may be constructed from urethane, such as polyether-polyurethane or polyester-polyurethane, or any other material having similar properties capable of fulfilling the intended purpose as disclosed herein.

Operation of the illustrated embodiment of the invention with valve 48 in its blocking position is shown in FIG. 3. Valve 48 occupies its blocking position as shown when fuel vapour pressure in the fuel tank is relatively low. Float valve 102 may occupy the position as shown, blocking flow of liquid fuel and fuel vapour through inlet opening 88 if the liquid fuel level in the fuel tank is relatively high. Otherwise, float valve 102 will be moved to a position away from inlet opening 88 allowing passage of fuel vapour therethrough.

At relatively low tank pressures with float valve 102 moved away from inlet opening 88, a small volume of fuel vapour can pass through the inlet 88 to reach venting control chamber 62 to serve as a pressure signal for diaphragm 64.

However, at low tank pressures, the fuel vapour accumulating in venting control chamber 62 does not supply sufficient force to diaphragm 64 to move diaphragm 64 away from its static position as shown in FIG. 3. Valve 48 thus remains in its blocking position preventing flow of fuel vapour through upper chamber 27 along vent path 37.

As shown in FIG. 2, at higher tank pressures, the fuel vapour pressure signal in venting control chamber 62 applies sufficient force to diaphragm 64 to move diaphragm 64 to its actuating position, in turn moving valve 48 from its blocking position to its venting position.

Once valve 48 has been urged into the venting position, fuel vapour can flow along vent path 37 through housing 12 to outlet 36, and then to vapour canister 22 and from there on to the engine 32 if the engine controller 26 so demands. Valve 48 will remain in this venting position until the fuel vapour pressure in the fuel tank is reduced to a predetermined level.

As the fuel vapour pressure in the fuel tank is reduced through venting, the pressure in venting control chamber 62 is of course also reduced. The force applied by fuel vapour in venting control chamber 62 diminishes to the point at which it becomes insufficient to maintain diaphragm 64 in the actuating position. Diaphragm 64 thus begins to return to its static position shown in FIG. 3.

Rollover valve assembly 31 is designed to quickly move to a closed position preventing flow of fuel vapour and liquid fuel through inlet opening 88 when exposed to sloshing or vertical surges of liquid fuel. The term "sloshing" as used herein refers to the tendency of liquid fuel to form waves moving essentially horizontally in response to vehicle movement. The foam block signifi-

cantly reduces the occurrence of liquid fuel contacting the rollover valve assembly 31 or the valve inlet 35. Vapour can easily flow through the foam material with an insignificant pressure drop, due to the open cell structure. However, liquid does not readily pass through the foam material, as the surface tension of the liquid blocks the small cellular openings in the foam. This liquid then seeps back into the tank after a short period of time, allowing fuel vapours to pass through the foam with insignificant restriction. Thus, the open cell foam is capable of restricting the flow of liquid fuel, while allowing relatively unrestricted fuel vapour flow.

The foregoing description presents a the preferred embodiment of the present invention. Details of construction have been shown and described for purposes of illustration rather than limitation. For instance, the housing 12 may only include a single valve, operative as a rollover valve, rather than the advance dual valve design illustrated herein.

#### Claims

1. A fuel tank vapour control apparatus for controlling the flow of liquid and vapour through an aperture in a fuel tank (16), the fuel tank vapour control apparatus comprising:
  - a vent housing (12) mounted in the aperture and formed to include a vent inlet (13) and a vent outlet (36), the vent housing (12) defining a vent path for communicating vapour from the fuel tank (16) between said vent inlet (13) and said vent outlet (36);
  - a valve (48) movable in said vent housing between a blocking position blocking flow of liquid and vapour from the fuel tank (16) between said vent inlet (13) and said vent outlet along said vent path and a venting position allowing flow of vapour between the fuel tank (16) and said vent outlet (36) along said vent path; and
  - a labyrinthine member (140) disposed between the fuel tank (16) and said vent path allowing vapour to flow in said vent path and blocking liquid flow in said vent path.
2. A fuel tank vapour control apparatus according to Claim 1, wherein said labyrinthine member (140) is constructed from foam.
3. A fuel tank vapour control apparatus according to Claim 2, wherein said foam member (140) envelopes said vent inlet (13) of said vent housing.
4. A fuel tank vapour control apparatus according to Claim 3, wherein said vent housing further comprises a barb (142) for attaching said foam member (140) to said vent inlet (13) of said vent housing.
5. A fuel tank vapour control apparatus according to any one of Claims 2 to 4, wherein said foam member (40) comprises an open cell foam.
6. A fuel tank vapour control apparatus according to Claim 5, wherein said open cell foam is preferably greater than 90% open.
7. A fuel tank vapour control apparatus according to any one of Claims 2 to 6, wherein said foam member (140) occupies substantially all of the fuel tank (16).
8. A fuel tank vapour control apparatus for controlling the flow of liquid and vapour fuel through an aperture in a fuel tank (16) for use in a motor vehicle having an internal combustion engine, the fuel tank vapour control apparatus comprising:
  - a vent housing (172) mounted in the aperture and formed to include a vent inlet (13) and a vent outlet (36), the vent housing (12) defining a vent path for communicating vapour from the fuel tank (16) between said vent inlet (13) and said vent outlet (36);
  - a vapour canister (122) having a canister inlet (18) in communication with said vent outlet (36) and a canister outlet (20) in communication with an intake manifold (30) on the internal combustion engine (32); and
  - a foam member (140) disposed between the fuel tank and said vent path allowing vapour to flow in said vent path and blocking liquid flow in said vent path.
9. A fuel tank vapour control apparatus according to Claim 8, wherein said foam member (140) envelopes said vent inlet (13) of said housing (12).
10. A fuel tank vapour control apparatus according to either Claim 8 or Claim 9, wherein said vent housing (12) further comprises a barb (142) for attaching said foam member (140) to said vent inlet (13) of said housing (12).




FIG. 1




FIG. 2




FIG. 4






FIG.3



2, 000



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 869 022 A3**

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
15.03.2000 Bulletin 2000/11

(51) Int. Cl.7: **B60K 15/035, F02M 25/08**

(43) Date of publication A2:  
07.10.1998 Bulletin 1998/41

(21) Application number: 97310702.2

(22) Date of filing: 31.12.1997

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: 31.03.1997 US 829664


(71) Applicant: **Ford Motor Company**  
Dearborn, MI 48126 (US)

(72) Inventors:  
• **Stringfellow, George Francis**  
Dearborn Heights, Michigan 48127 (US)  
• **Ayers, Douglas William**  
Milan, Michigan 48160 (US)  
• **Nulman, Mark**  
West Bloomfield, Michigan 48322 (US)

(74) Representative:  
**Messulam, Alec Moses et al**  
**A. Messulam & Co.**  
24 Broadway  
Leigh-on-Sea Essex SS9 1BN (GB)

### (54) Fuel tank vapour control apparatus

(57) A fuel tank vapour control apparatus controls the flow of liquid and vapour fuel through an aperture in a fuel tank (16). The fuel tank vapour control apparatus includes a vent housing (12) mounted in the aperture (34) and formed to include a vent inlet (13) and a vent outlet (36), the vent housing (12) defining a vent path for communicating vapour fuel from the fuel tank between the vent inlet and the vent outlet. The apparatus also includes a valve (48) movable in the vent housing between a blocking position for blocking flow of liquid and vapour fuel from the fuel tank between the vent inlet and the vent outlet along the vent path and a venting position allowing flow of vapour fuel between the fuel tank and the vent outlet along the vent path. A labyrinthine member (140) is also included, being disposed between the fuel tank and the vent path for discriminating fuel vapour from liquid fuel so as to block liquid fuel from the vent path.



**FIG.2**

EP 0 869 022 A3



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 97 31 0702

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	DE 196 21 031 A (WALBRO CORP) 16 January 1997 (1997-01-16)	1	B60K15/035 F02M25/08
A	* column 3, line 57 - column 4, line 5 * ---	8	
X	GB 2 299 073 A (PORSCHE AG) 25 September 1996 (1996-09-25)	1	
A	* page 4, line 12 - line 27 * ---	8	
A	EP 0 330 864 A (OPEL ADAM AG) 6 September 1989 (1989-09-06) * claim 1 *	1,2,8	
A	US 5 234 013 A (ROETKER JOHN J ET AL) 10 August 1993 (1993-08-10) * figure 1 * -----	1,8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B60K F02M
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 20 January 2000	Examiner Tamme, H-M
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03/82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 31 0702

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-01-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19621031 A	16-01-1997	FR 2736592 A	17-01-1997
		JP 9032671 A	04-02-1997
GB 2299073 A	25-09-1996	DE 19510821 A	02-10-1996
		FR 2731955 A	27-09-1996
		US 5687753 A	18-11-1997
EP 0330864 A	06-09-1989	DE 3806252 C	27-07-1989
		JP 1267350 A	25-10-1989
US 5234013 A	10-08-1993	DE 69301732 D	11-04-1996
		DE 69301732 T	02-10-1996
		EP 0649506 A	26-04-1995
		JP 7508815 T	28-09-1995
		WO 9401705 A	20-01-1994



2, 1994



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 25 1492

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 6 170 510 B1 (KING TIMOTHY J ET AL) 9 January 2001 (2001-01-09) * abstract *	1	B60K15/035 B60K15/03
X	EP 0 976 597 A (PLASTIC OMNIUM CIE) 2 February 2000 (2000-02-02) * figure *	1	
A	US 6 062 276 A (BENJEY ROBERT P ET AL) 16 May 2000 (2000-05-16) * figures *	1	
A	EP 0 869 022 A (FORD MOTOR CO) 7 October 1998 (1998-10-07) * the whole document *	1	
A	US 5 582 198 A (NISHI HIROSHI ET AL) 10 December 1996 (1996-12-10) * the whole document *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B60K F02M
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 8 April 2003	Examiner Tamme, H-M
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	



012 1 2 4





**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 1492

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-04-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 6170510	B1	09-01-2001	US	5944044 A	31-08-1999
			EP	1007872 A1	14-06-2000
			WO	9850717 A1	12-11-1998
EP 0976597	A	02-02-2000	FR	2781728 A1	04-02-2000
			BR	9902999 A	08-08-2000
			EP	0976597 A1	02-02-2000
US 6062276	A	16-05-2000	US	5860458 A	19-01-1999
			US	5590697 A	07-01-1997
			US	6206057 B1	27-03-2001
			US	5983958 A	16-11-1999
			CA	2198008 A1	29-02-1996
			DE	69515122 D1	23-03-2000
			DE	69515122 T2	14-12-2000
			DE	69525070 D1	21-02-2002
			DE	69525070 T2	05-09-2002
			EP	0777833 A1	11-06-1997
			EP	0845624 A2	03-06-1998
			JP	10506696 T	30-06-1998
			JP	3150702 B2	26-03-2001
			WO	9606294 A1	29-02-1996
			US	5755252 A	26-05-1998
			US	5797434 A	25-08-1998
EP 0869022	A	07-10-1998	US	5836341 A	17-11-1998
			EP	0869022 A2	07-10-1998
US 5582198	A	10-12-1996	JP	2853572 B2	03-02-1999
			JP	7301353 A	14-11-1995



11-11-11

11-11-11

11-11-11